

NPDV20C16A

(NiveoProfessional SmartPDU, vertical, 0U, 16A load, 20xC13, 4xC19, overall metered and switched)

More information:
WWW.NIVEOPROFESSIONAL.COM

All rights reserved Netstar Products BV 2013

Product Specification

Features

0U	Aluminium case, 0U, Vertical
Access methods	SNMP, Serial, Web
Metering data	Input voltage, total load current
Outlet types	IEC320C13, IEC320 C19
Alarm methods	E-mail. SNMP trap, flashing indicator on web interface, LED display, PDU buzz
Main monitoring data	Input voltage, total current, outlet state, environment state
Main controlling functions	Total current, outlet switching, sequential switching with delay, temperature and humidity monitoring, threshold exceeding alerts, centralized management
Centralized management	Management by SNMP

All rights reserved Netstar Products BV 2013

Main functions

Main Functions	Details	Function levels	
		Monitor	Control
Monitor	Total load current	✓	✓
	Input voltage	✓	✓
	Outlet state (on/off)	✓	✓
	System operating state (RUN indicator)	✓	✓
	Temperature and humidity state	✓	✓
Control	Outlet switching		✓
	Delay of outlet sequential switching		✓
System reset	Return to outlet setting after reset		✓
Automatic user defined alarm	Threshold of total current	✓	✓
Alarm	RUN indicator on controlling panel flashes and buzzes		
	Automatic email alert to administrator		
	Trap alarm by SNMP		
Accessing method	Web, access via IE		
	SNMP V1		
	Serial, Modbus protocol		
Software	Support web browsers like IE, Firefox, Google		

Main Functions	Details	Parameters
Input characteristics	Rated input voltage	110/220VAC 50/60 Hz
	Max. load current	16A
	Cable specification	3x1,5mm/ 3x2.5mm2
	Cable length	2,5m
	Output voltage	110/220VAC
	Outlet number	24
	Sensor port	T/H1
	Serial port	Serial control
Physical properties	Product dimension	L:1823mm W:66.6mm H: 44,4mm
	Case material	Aluminium
	Case color	Black
	Mounting method	Both end brackets
	Standard fittings	1 x RJ45 network wire
Environment characteristics	Working environment	Temperature: 0 – 50℃ Humidity: 5 – 95 %

All rights reserved Netstar Products BV 2013