

NPM8C16A

(Niveo Professional Switched 19” PDU, 16A load, 8xC13)

More information:
WWW.NIVEOPROFESSIONAL.COM

All rights reserved Niveo International BV 2015

Met opmaak: Kop 1

Introduction

Niveo Professional Power Distribution Units facilitate the control and monitoring of the power in your network. The NPM8C16A Switched PDU allows remote switching (on and off) to each outlet and configuration of power-on delays via sequential switching. The total load current, status of outlets, temperature (option) can be monitored and an alarm may be sent when a predefined threshold is exceeded. Niveo Professional PDU's come with a free bundle of monitoring software, allowing optimal remote service and contributing to energy saving protocols.

True RMS Current Meter
To get accurate current

Power monitor
The NPM8C16A can monitor, Total Current by Meter. It can be accessed over Web and SNMP. A free monitoring software tool is included.

Protocols
The NPM8C16A uses following protocols: Http, Https, SNMP, DHCP, UDP.

Outlet Control
All 8 outlets of the NPM8C16A PDU can be controlled individually

Power Delay
Sequence of Power On/Off can be pre-defined.

Alarm Thresholds
User defined Alarm thresholds for Warning and Overload

Event Alert
Event alert by Email, Trap, Audible alarm

Temp./Humidity
Optional accessory

All rights reserved Niveo International BV 2015

Technical Specifications

Output	8 x IEC320 C13
Input	IEC 320 C20 Inlet IEC 320 C19 to NEMA C20 power cord , 3 meters
Protection:	16 AMP Circuit Breaker
LED Indicators	SSL: 1 Yellow LED DHCP: 1 Green LED Output Status: 1 Green LED Circuit Status Red LED
Network Port	1 RJ45
Temp./Humidity	1 RJ11 for ENV probe connection
PDU ID	**1** Digits seven segments for PDU identification
Current Meter	3 Digits Seven Segments for True RMS Meter Range:0A~20A Resolution: 0,1 A Precision: +/- 2% +/- 0,1AMP
Nominal Voltage	230V
Dimensions	90 x 432 x 44 mm (L x W x H)
Weight	3 kg
Operating Temperature	0 to 40°C
Max. Output Current	16 Amp (UL derated 12 Amp)
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC, c-UL-us, CE, ROHS

All rights reserved Niveo International BV 2015

niveo professional